

990 C Combination Lock



Legge's 990 C Combination Mortice Lock has been designed specifically to meet the requirements of the Australasian market. The 990 C is ideally suited for commercial, industrial, institutional and government buildings, where durability and security are of major importance.

The 990 C has a high purity die cast zinc alloy case to provide rigidity and precision. Major internal components are made of either stainless steel or sintered steel/ copper alloy to provide durability and strength.



Features

- Multi-function case allows easy conversion of a vestibule lock function (inside handle free) to a combination lock function (both handles locked) by a simple external operation
- Reversible stainless steel latch adjusts for inwards/ outwards opening and left/right hand without case disassembly
- Standard lock suitable for doors 32mm to 50mm thick. Extended cylinders, spindles and strike plates available to accommodate thicker doors and wider jambs
- 990MF case will accept bolt-through fixing for 50.8mm diagonal and 38mm-41mm horizontal fixing door furniture
- Follower will accept 7.6mm-8mm furniture spindles, with no adjustment necessary
- A threaded pin is used for secure cylinder retention
- Designed to be compatible with FES20M and FES90M-P electric strikes

Warranties		
Mechanical	30 years	



Specification guide

	Function	Sub-function	Finish	Backset		
	Combination lockL9C	Entry lockC1 Sliding door lockC7 Entry lockC21 Turn entry lockC23 Double cylinder lockC27 Single cylinder lockC31 Privacy latchC33 Passage latchC57	Antique Bronze	60mmrefer to 991 70mm70 89mm89 127mm127		
1.	1. Function Select the desired function e.g., Combination door lock					
2.	 Sub-function Select the required sub-function e.g., C1 Combination door lock					
3.	3. Finish Select the desired finish e.g., Satin chrome plate					

Finishes







Security: Rated S8 and SL8 for physical security, SC7-SC8 for cylinder





security and K6 for keying security Corrosion:


Rated C7 for corrosion

Durability: ∕⊧ Rated D8 for durability










15mm





- Key or turn locks or unlocks both handles simultaneously
- Deadlatching engages when door is in closed position
- Reversible bolt for handing

Specifications

Door type	Timber or metal
Door thickness	32mm to 50mm standard, extended cylinders, spindles and strike plates available to accommodate thicker doors
Lock case	High purity zinc alloy
Outer forend	Stainless steel or brass
Inner forend	Stainless steel
Bolt	Stainless steel
Sub-bolt	Stainless steel
Spindles	2 split spindles 32mm
Strike plate	Stainless steel or brass 45mm standard. 40mm, 50mm, 60mm, 70mm, 80mm & 90mm available
Backsets	60mm (refer to Legge 991), 70mm, 89mm and 127mm available
Key cylinder	C4 6 Pin keyway standard, Schlage C6 pin keyway optional, Schlage SR1 Restricted keyway optional, Schlage Everest Open & Restricted keyways optional









Legge 990 C Combination Lock

Sub-function	Cams and adaptors
C1 - Entry lock (singles entry) Outside: Key operates bolt at all times. Both handles operative except when locked by inside turn Inside: Turn locks and unlocks both handles	l ⊙ □ □ □

Outside: Key operates bolt at all times. Both handles operative except when locked by inside key Inside: Key locks and unlocks both handles

2

9A

1A

C21 - Entry lock

Outside: Both handles operative except when locked by outside key or inside turn Inside: Turn locks and unlocks both handles

C23 - Turn entry lock

Outside: Both handles operative except when locked by outside key Inside: Turn operates bolt at all times

C27 - Double cylinder lock

Outside: Handle operative except when locked by outside or inside key Inside: Handle operative except when locked by inside or outside key



2

Legge 990 C Combination Lock

Sub-function

C31 - Single cylinder lock

Outside: Both handles operative except when locked by outside key Inside: Handle operative except when locked by outside key

C33 - Privacy latch

Outside: Operative except when locked by inside turn. Emergency button unlocks both handles Inside: Turn locks and unlocks both handles

C57 - Passage latch

Outside: Always operative Inside: Always operative





Cams and adaptors









Legge 990 C Cams and Cam Adaptors



1A (with adaptor)







5


9A (with adaptor)



Legge 990MF Series accessories

R13 Rebate kit

This kit adapts latches and strikes for 13mm rebated door preparations **Finishes:** Satin Stainless Steel or for special finishes available, refer to page 2



Non-standard strikes

Component Variants					
Description	А	В			
LL40 Ext Striker	40	32			
LL50 Ext Striker	50	42			
LL60 Ext Striker	60	52			
LL70 Ext Striker	70	62			
LL80 Ext Striker	80	72			
LL90 Ext Striker	90	82			

